

**SPECIFICATION CHART – THREE PHASE TRANSFORMER LAMINATION (E & I)**

LAMINATION DIMENSIONS ( MM )								Holes		
Type No.	A	B	C	D	E	F	G	No.	Dia	Distance
15	12.7	76.2	63.5	12.7	12.7	38.1	19.1	4	5.5	50.0
33	14.0	84.0	70.0	14.0	14.0	42.0	21.0	4	5.5	63.5
3	15.9	95.3	79.4	15.9	15.9	47.6	23.9	4	6.0	79.3
16 or 4	19.1	114.3	95.3	19.1	19.1	57.2	28.5	4	6.0	95.0
43 or 7	25.4	152.4	127.0	25.4	25.4	76.2	38.1	4	7.0	127.0
8	25.4	184.5	171.5	25.4	25.4	120.7	54.2	4	9	159.5
8 B	38.1	235.0	196.9	38.1	38.1	120.7	60.0	4	10.0	197.0
100	50.8	355.6	254.0	50.8	50.8	152.4	101.6	6	12.5	
S10 M	50.8	257.5	203.2	50.8	50.8	101.6	52.6	4	10.0	197.0
E201	34.3	201	80	34.3	34.3	45.9	49	6	10 & 5	E only
E251	47.3	250.5	95.5	47.3	47.3	48.2	54.5	6	10 & 5	E only
S12	50.8	304.8	254.0	50.8	50.8	152.4	76.2	6	12.7	
S197	38.1	197.0	197.0	38.1	38.1	120.7	41.3	4.0	10.0	
S150	30.0	150.0	150.0	30	90	30	30	6	7.0	
S122	44.5	222.5	222.5	44.5	133.5	44.5	44.5	6	12.7	
6	19.1	127.0	114.3	19.1	19.1	76.2	34.8	4	6.2	

Special Features :

- 1) International Quality & Technology
- 2) Long EI are also available in types No. 33, 3, 15, 7, 8b etc.
- 3) We undertake Tailor made jobs also.
- 4) Lamination are manufactured only from the Electrical Steel Grade under which they are listed I.e C.R.N.O.
- 5) Lamination are available with Air gap on center limb for choke application
- 6) Type 15, 33, 30 are also available without holes on request.
- 7) Strips as per customer specification without holes on request.  
Use core filler machines.

